



EASY 24

The mobile solution

The SmokeCloak® **EASY 24** is designed and developed specifically for vehicle usage. This vehicle unit is targeted at companies who transport desirable or high-value goods such as drugs, cigarettes, electronics, alcohol and cash.

The EASY 24V has a heavy duty sabotage resistant case.



- Danish design
- Fluid refill system
- Built-in self diagnostics
- Seamless integration with all existing alarm systems



Product features

- Very high output of dense white fog for maximum protection
- Harmless dry vapour with no negative side effects
- The fog hangs up to an hour
- Fluid refill system
- Danish design
- Heavy duty sabotage resistant case
- Internal system status LED indicators
- Built-in self diagnostics
- Electronic fluid measurement system
- Output signals for communication with existing alarm system
- Input signals for controlling the SmokeCloak from an existing alarm system Installation
- Installation, service and maintenance friendly
- Seamless integration with all existing alarm systems



EASY 24

Physical

Dimensions	192 x 182 x 62 mm
Installation Weight	< 14 kg
Colour	White RAL 9016
Fluid	1 litre fluid refill system
Required electricity supply	24VDC
Power consumption	320W@24V
Average power consumption	75W
Reaction time	0,1 seconds
Output	00 m3 / 30 sec. depending on the application (requirement to the visibility)
Pulse Function	Programmable via Dip switch
Heat up time	(ready) 42 min