



EASY 24

The mobile solution

The SmokeCloak® **EASY 24** is designed and developed specifically for vehicle usage. This vehicle unit is targeted at companies who transport desirable or high-value goods such as drugs, cigarettes, electronics, alcohol and cash.

The EASY 24V has a heavy duty sabotage resistant case.



- Danish design
- Fluid refill system
- Built-in self diagnostics
- Seamless integration with all existing alarm systems



Product features

- Very high output of dense white fog for maximum protection
- Harmless dry vapour with no negative side effects
- The fog hangs up to an hour
- Fluid refill system
- Danish design
- Heavy duty sabotage resistant case
- Internal system status LED indicators
- Built-in self diagnostics
- Electronic fluid measurement system
- Output signals for communication with existing alarm system
- Input signals for controlling the SmokeCloak from an existing alarm system Installation
- Installation, service and maintenance friendly
- Seamless integration with all existing alarm systems



EASY 24

Physical

| | |
|-----------------------------|--|
| Dimensions | 192 x 182 x 62 mm |
| Installation Weight | < 14 kg |
| Colour | White RAL 9016 |
| Fluid | 1 litre fluid refill system |
| Required electricity supply | 24VDC |
| Power consumption | 320W@24V |
| Average power consumption | 75W |
| Reaction time | 0,1 seconds |
| Output | 00 m3 / 30 sec. depending on the application (requirement to the visibility) |
| Pulse Function | Programmable via Dip switch |
| Heat up time | (ready) 42 min |